
	CONCRETE LINTEL SCHEDULE  MIN. DEPTH LINTEL REINFORCEMENT REBAR BELOW OPENING  2" FOR EACH 1" OF OPENING WIDTH, 6" MIN.  NOTE: MAX. LINTEL LENGTH IS 6"-0". EXTEND ALL REBAR 24" MIN. PAST OPENING (TYP.)  DESIGNATION HOLDOWN AND STRAP SCHEDULE  DESIGNATION HOLDOWN OR STRAP MIN. STHD8 / 8RJ 2  WIDTH, 6" MIN.  NOTE: MAX. LINTEL LENGTH IS 6"-0". EXTEND ALL REBAR 24" MIN. PAST OPENING (TYP.)  AAA STHD8 / 8RJ 2  WIDTH, 6" MIN. STHD8 / 8RJ 2  WIDTH MAX. LINTEL LENGTH IS 6"-0". EXTEND ALL REBAR 24" MIN. PAST OPENING (TYP.)	MARK WIDTH HEIGH SIZE GRADE SPACING SIZE GRADE SPACING FIT 20° CONT. 10° SIZE LENGTH SPACING NO. SIZE
TOP OF FIG. 671-0.7  SEE STATE	TOP OF FTG (FTG)  15.5"  16.7"  TOP OF WALL (FW)  15.5"  16.7"  TOP OF WALL (FW)  15.5"  16.7"  TOP OF WALL (FW)  15.5"  TOP OF FTG (FTG)  TOP OF FTG (FTG)  TOP OF WALL (FW)  TOP OF WALL (FW)	TOP OF WALL (PWID)  TOP OF WALL (PWID)  TOP OF WALL (PWID)  TOP OF WALL (PWID)  TOP OF FIG (FTIC)  H = 807  TOP OF WALL (PWID)  EL = 1007  TOP OF WALL (PWID)
1/2" Ø ANCHOR BOLTS @ 16" O.C.  15-4"  14'-3"  11'  20	EL. = 88'	



REDWOOD ENGINEERINGInc. 291 E. 950 S. OREM,UTAH 84058 P: 801.426.6500 E: info@redwoodeng.com www.redwoodeng.com

FOOTING AND FOUNDATION PLAN

REVISION

DATE

PROJECT NO:

DRAWN BY:

CHECKED BY:

STAMP