



1. ALL CEILING HEIGHTS INDICATED ON PLANS ARE FROM TOP OF FINISH FLOOR TO UNDERSIDE OF FINISH CEILING U.O.N.
2. SEE A6-1 FOR SUSPENDED GYP. BD. CEILING DETAIL.
3. PROVIDE ADEQUATE CLEARANCES FOR FIXTURES, DUCTS, CEILINGS AND RELATED PERTINENT ITEMS NECESSARY TO MAINTAIN THE SPECIFIED CEILING HEIGHT ABOVE THE FINISH FLOOR.
4. ARCHITECTURAL DRAWINGS DETERMINE THE LOCATION OF LUMINAIRES AND SUPERCEDES ALL OTHER DRAWINGS U.O.N.
5. SEE ELECTRICAL DRAWINGS FOR FIXTURE MODEL NUMBER.
6. ALL LIGHTING FIXTURES PROVIDED BY OWNER AND INSTALLED BY SUBCONTRACTOR U.O.N.
7. LATERAL BRACING FOR CEILING MUST BE PROVIDED, WHERE CEILING LOADS ARE LESS THAN 5PSF AND NOT SUPPORTING INTERIOR PARTITIONS. CEILING BRACING SHALL BE PROVIDED BY FOUR NO. 12 GA. WIRES SECURED TO THE MAIN RUNNER WITHIN 2 INCHES OF THE CROSS RUNNER INTERSECTION AND SPAYED 90 DEGREES FROM EACH OTHER AT AN ANGLE LESS THAN OR EQUAL TO 45 DEGREES FROM THE PLANE OF THE CEILING THESE HORIZONTAL RESTRAINT POINTS SHALL BE PLACED 12 FEET O.C. IN BOTH DIRECTIONS WITH THE FIRST POINT WITHIN 4'-0" FROM EACH WALL. ATTACHMENT OF THE RESTRAINT WIRES TO THE STRUCTURE ABOVE SHALL BE ADEQUATE FOR THE LOAD IMPOSED.
8. ADDITIONAL HANGARS AND SAFETY WIRES FOR LIGHT FIXTURES, SPEAKERS AND AIR SUPPLY/RETURN DIFFUSERS (PER LOCAL CODES) TO BE THE RESPONSIBILITY OF THE CEILING SUB-CONTRACTOR.
9. PROVIDE ACCESS PANELS AS REQUIRED, BY CODE, COORDINATE LOCATIONS WITH ARCHITECT.
10. ALL GYP. BD. CEILINGS TO BE SMOOTH FINISH & PAINTED U.O.N.
11. ALL MEASUREMENTS ARE TO THE CENTER OF THE FIXTURE U.O.N.
12. ALL EXPOSED CONDUITS TO BE MOUNTED TIGHTLY TOGETHER.
13. TOUCH UP PAINT OF ALL LIGHT FIXTURES, STEMS, & SCREWS AFTER RETHREADING; PAINT COLOR TO MATCH STEM.
14. ALL HATCHED SYMBOLS DENOTE EMERGENCY FIXTURE.
15. GC TO REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.

KEY NOTES 3

SEE LEGEND A3-0 FOR CEILING ELEMENTS

SCHEMATIC LOCATION OF UNISTRUT AT 10'-0" O.C. PER MANF REQUIREMENTS

LINE OF UNISTRUT

SPLICE LOCATION SHOWN PERPENDICULAR

SCHEMATIC LOCATION OF UNISTRUT SUPPORT LOCATION AT 8'-0" O.C. PER MANF REQUIREMENTS

LINE OF UNISTRUT

SUPPORT DROP

SCHEMATIC LOCATION OF UNISTRUT SUPPORT AND SPLICE LOCATION

LINE OF UNISTRUT

SUPPORT DROP AND UNISTRUT SPLICE OVERLAP

NOTE: MINIMIZE UNISTRUT SUPPORT DROPS WHILE MAINTAINING UNIFORMITY AND CONSISTENCY AS POSSIBLE.

CONDUIT INSTALLATION GUIDELINES (OPEN CEILING AREAS):

- CONDUIT TO BE INSTALLED PARALLEL AND/OR PERPENDICULAR TO DEMISING WALLS.
- CONDUIT TO BE INSTALLED TIGHT TO STRUCTURE.
- CONDUIT THAT DOES NOT SERVE LIGHTING/EQUIPMENT IN THE OPEN CEILING AREA, TO BE RUN WITHIN WALLS.
- CONDUIT DROPS SHALL BE TIGHT TO THREADED ROD OR OTHER STRUCTURAL ELEMENTS
- MULTIPLE CONDUIT RUNS SHALL BE GROUPED TOGETHER.

GENERAL NOTES 2

NEW STORE

ATHLETA

GAP INC.
STORE DEVELOPMENT
2 FOLSOM STREET
SAN FRANCISCO, CA 94105

ORACLE ID: 140261

STORE NUMBER: 7341

STORE LOCATION: STATION PARK
230 NE PROMONTORY
SPACE C-120
FARMINGTON, UT 84025

DESIGN TYPE: DERBY B
GENERATION: 21Q34
PROTOTYPE DATE: 1/8/2021
OPENING: 2021

ARCHITECT INFO:

brr

ARCHITECT OF RECORD:
MARTIAH MEYER
8131 METCALF AVE
SUITE 300
OVERLAND PARK, KS 66204
www.brrarch.com
TEL: 913-262-9095
FAX: 913-262-9044

CONSULTANT INFO:

PROFESSIONAL STAMP:

ISSUE TYPE:

LL/PERMIT/BID: 02/19/21

REVISIONS:

DRAWN BY: KDA
A/E JOB NUMBER: 65011072

TITLE SHEET:

REFLECTED CEILING PLAN
– UNISTRUT PLAN

SHEET NUMBER:

A3-0B