

- 3.1 INSTALLATION
- A. COORDINATE WITH THE WORK OF OTHER TRADES TO ASSURE PROPER PROVISIONS FOR INTERFACE WITH INSTALLATION.
- B. INSTALL MOBILE STORAGE SHELVING IN STRICT ACCORDANCE WITH THE RECOMMENDATIONS OF THE MANUFACTURER.
- C. FLOORING SHALL BE SMOOTH, FLUSH AND LEVEL. ALL TRACKS SHALL BE LEVELED AND ALL GAPS BETWEEN TRACK AND FLOOR FILLED WITH FAST SETTING CEMENTS AS RECOMMENDED BY MANUFACTURER TO FORM A SOLID BASE. ALL TRACKS SHALL BE ANCHORED TO SUBFLOOR.
- D. LOCATE AND POSITION RAILS PROPERLY, LEVELED AND GROUTED, ALLOWING A MINIMUM OF 1/4" FOR GROUT UNDER HIGH POINT. WORK GROUT UNDER RAIL, FILL ANY VOIDS COMPLETELY AND TRIM SIDES FLUSH WITH RAILS.
- E. UPON COMPLETION OF THE INSTALLATION, PUT MOBILE STORAGE SHELVING THROUGH AT LEAST 10 COMPLETE CYCLES OF OPERATION.
- 3.2 PROTECTION
- A. AFTER INSTALLATION, CLEAN SURFACES IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. PROTECT SURFACES OF SHELVING WITH KRAFT PAPER OR OTHER SUITABLE COVERING.
- 3.3 PROTECTION AND CLEANING
- A. PROTECT MOBILE STORAGE SHELVING TO ENSURE PROPER OPERATING CONDITION. REPAIR OR REPLACE DAMAGED UNITS AS DIRECTED BY THE OWNER'S PROJECT MANAGER.

END OF SECTION 10 56 26

SECTION 10 69 00 - MANAGER'S OFFICE AND STOCKROOM ACCESSORIES

- A. SUMMARY
1. SECTION INCLUDED 1. INSTALLATION OF STOCKROOM ACCESSORIES AT LOCATIONS SHOWN ON PLANS.
- B. MANUFACTURERS
1. ASI (814-479-9000)
2. TRIMCO (203-262-4191)
3. FELLOWES
- C. MATERIALS
1. DOOR STOP: TRIMCO 1231 B. KEYBOARD TRAY: FELLOWES MODEL # 940301 PART
- D. INSTALLATION
1. INSTALL IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND INSTRUCTIONS. LEVEL, PLUMB, SECURE TO STRUCTURE IN ACCORDANCE WITH LOCAL SEISMIC STANDARDS.
2. BOLT MANAGER'S SAFE TO FLOOR. LOCATE PER ARCHITECTURAL DRAWINGS.
3. INSTALL DOOR STOP FOR SAFE DOOR. LOCATE PER ARCHITECTURAL DRAWINGS.
4. INSTALL KEYBOARD TRAYS AT MANAGER'S OFFICE COUNTER.

END OF SECTION 10 69 00

SECTION 12 48 13 - ENTRY MAT

PART 1 - GENERAL

- 11 SUMMARY
- A. THIS SECTION INCLUDES:
1. RECESSED COCOA MATS
- 12 COORDINATION
- A. INTERIOR RECESSED MATS CONCEAL OWNER'S SECURITY SYSTEM. COORDINATE SIZE, LOCATION, DEPTH AND INSTALLATION WITH SECURITY SYSTEM REQUIREMENTS.
- 13 QUALITY ASSURANCE
- A. ACCESSIBILITY REQUIREMENTS: COMPLY WITH "AMERICANS WITH DISABILITIES ACT (ADA), ACCESSIBILITY GUIDELINES FOR BUILDINGS AND FACILITIES (ADAAG)" AND REQUIREMENTS OF AUTHORITIES HAVING JURISDICTION.

PART 2 - PRODUCTS

21 MATERIALS

- 22 SEE SCHEDULE FABRICATION
- A. FLOOR MATS: SHOP FABRICATE UNITS TO THE GREATEST EXTENT POSSIBLE.
1. IF NOT OTHERWISE INDICATED, PROVIDE SINGLE UNIT FOR EACH MAT INSTALLATION; DO NOT EXCEED MANUFACTURER'S RECOMMENDED MAXIMUM SIZES FOR UNITS THAT ARE REMOVED FOR MAINTENANCE AND CLEANING.
2. WHERE JOINTS IN MATS ARE NECESSARY, SPACE SYMMETRICALLY AND AWAY FROM NORMAL TRAFFIC LANES.

PART 3 - EXECUTION

- 3.1 PREPARATION
- A. EXAMINE FLOOR CONDITIONS FOR COMPLIANCE WITH LOCATION AND SIZE REQUIREMENTS. PROCEED WITH INSTALLATION ONLY AFTER UNSATISFACTORY CONDITIONS HAVE BEEN CORRECTED.
- 3.2 FLOOR MAT INSTALLATION
- A. INSTALL RECESSED MAT FRAMES TO COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS. SET MAT TOPS AT HEIGHT RECOMMENDED BY MANUFACTURER FOR MOST EFFECTIVE CLEANING ACTION; COORDINATE TOP OF MAT SURFACES WITH BOTTOM OF DOORS THAT SWING ACROSS MATS TO PROVIDE CLEARANCE BETWEEN DOOR AND MAT.
1. INSTALL GROUT AND FILL AROUND FRAMES AND, IF REQUIRED TO SET MAT TOPS AT PROPER ELEVATIONS, IN RECESSES UNDER MATS. FINISH GROUT AND FILL SMOOTH AND LEVEL. COMPLY WITH REQUIREMENTS SPECIFIED IN DIVISION 3 FOR GROUT AND FILL.
- 3.3 PROTECTION
- A. AFTER COMPLETING FRAME INSTALLATIONS, PROVIDE TEMPORARY FILLER OF PLYWOOD OR FIBERBOARD IN FOOT GRILLE OR MAT RECESSES AND COVER FRAMES WITH PLYWOOD PROTECTIVE FLOORING. MAINTAIN PROTECTION UNTIL SUBSTANTIAL COMPLETION.

END OF SECTION 12 48 13

NEW STORE



GAP INC.
STORE DEVELOPMENT
2 FOLSOM STREET
SAN FRANCISCO, CA 94105

ORACLE ID:

140261

STORE NUMBER:

7341


STORE LOCATION:

STATION PARK

230 NE PROMONTORY
SPACE C-120
FARMINGTON, UT 84025

DESIGN TYPE: DERBY B
GENERATION: 21Q34
PROTOTYPE DATE: 1/8/2021
OPENING: 2021

ARCHITECT INFO:



ARCHITECT OF RECORD:
MARIAH MEYER
8131 METCALF AVE
SUITE 300
OVERLAND PARK, KS 66204
www.brrarch.com
TEL: 913-262-9095
FAX: 913-862-9044

CONSULTANT INFO:

PROFESSIONAL STAMP:

ISSUE TYPE:

LL/PERMIT/BID: 02/19/21

REVISIONS:

DRAWN BY: KDA
A/E JOB NUMBER: 65011072

TITLE SHEET:

SPECIFICATIONS

SHEET NUMBER:

SP-13