

**A2 SITE ELECTRICAL PLAN**  
 ES101 SCALE: 1" = 20'-0"

**GENERAL SHEET NOTES**


- 1 THE ELECTRICAL CONTRACTOR SHALL MEET WITH AND COORDINATE WITH ALL SERVICE PROVIDERS (POWER, COMMUNICATION, CABLE/SATELLITE, ETC.) TO THE FACILITY ON SITE PRIOR TO ANY WORK BEING PERFORMED. CONFIRM WITH EACH SERVICE PROVIDER EXACT LOCATIONS EQUIPMENT AND ROUTING. COMPLY WITH ALL SERVICE PROVIDER'S CURRENT STANDARDS AND REQUIREMENTS. PROVIDE THE REQUIRED EQUIPMENT, RACEWAYS, BOXES, CABLE, ETC. AS REQUIRED BY THE SERVICE PROVIDER WEATHER SHOWN ON THE DRAWINGS OR NOT.
- 2 FOR ALL LIGHT FIXTURES, POLE LIGHTS, AND ALL OTHER ELECTRICAL DEVICES THE CONTRACTOR SHALL COORDINATE EXACT LOCATION AND MOUNTING HEIGHTS WITH ARCHITECT, OWNER, ENGINEER, AND ALL OF THE CONTRACT DOCUMENTS PRIOR TO ROUGH IN AND TRENCHING.
- 3 CONTRACTOR IS RESPONSIBLE FOR ALL TRENCHING, BACKFILL, AND COMPACTION ASSOCIATED TO ALL ELECTRICAL UNDERGROUND RACEWAYS AND CABLES. COORDINATE WITH ARCHITECTURAL AND CIVIL DRAWINGS. SEE UNDERGROUND RACEWAY DETAILS FOR REQUIREMENTS FOR EACH TRENCH.
- 4 CONTRACTOR SHALL INSTALL POLE MOUNTED LIGHTS IN STRAIGHT LINES, SQUARE, AND PLUMB. COORDINATE WITH ARCHITECT AND CIVIL DRAWINGS. CONTRACTOR SHALL INSTALL POLE MOUNTED LIGHTS IN STRAIGHT LINES, SQUARE, AND PLUMB. COORDINATE WITH ARCHITECT AND CIVIL DRAWINGS.
- 5 THE ELECTRICAL CONTRACTOR SHALL HAVE ANY AND ALL CONCRETE POLE BASES AND SLABS REVIEWED BY A STRUCTURAL ENGINEER AND SHALL MODIFY DESIGN PER STRUCTURAL ENGINEER'S AND OR AHJ'S RECOMMENDATIONS.
- 6 PROVIDE BATTERY PACKS IN ALL EXTERIOR FIXTURES ADJACENT TO EGRESS DOORS.
- 7 PROVIDE PHOTOCELL ON NORTH SIDE OF FACILITY TO CONTROL EXTERIOR LIGHTS.
- 8 ALL EXTERIOR RECEPTACLES SHOWN SHALL BE NEMA 5-20R GFCI "WEATHER RESISTANT" RECEPTACLE WITH "WEATHER PROOF IN-USE COVER."
- 9 THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR ALL CONCRETE/ASPHALT CUTTING AND REPLACEMENT OF CONCRETE/ASPHALT TO MATCH EXISTING ASSOCIATED WITH UNDERGROUND RACEWAYS PROVIDED AS PART OF THIS PROJECT.
- 10 REFER TO PLANS FOR CONSTRAINTS ON PHYSICAL DIMENSIONS AND CLEARANCE REQUIREMENTS OF EQUIPMENT. PROVIDE EQUIPMENT DIMENSIONS THAT FALL WITHIN THE CONSTRAINTS OF EACH SPECIFIC LOCATION.
- 11 PROVIDE SERVICE RATED EQUIPMENT AT EACH SERVICE ENTRANCE.
- 12 SERVICE EQUIPMENT SHALL BE LEGIBLY MARKED IN THE FIELD WITH THE MAXIMUM AVAILABLE FAULT CURRENT. VERIFY OR RE-CALCULATE THE AVAILABLE FAULT CURRENT AT THE SERVICE WHERE MODIFICATIONS TO THE ELECTRICAL INSTALLATION OCCUR. PLEASE INCLUDE NOTES IN THE ELECTRICAL DRAWINGS OR SUPPLY CALCULATIONS WHERE APPLICABLE. SEE NEC 110.24. (B)

**SHEET KEYNOTES**

- 1 EXISTING COMMUNICATIONS MANHOLE 'MH-18011-02'.
- 2 NEW COMMUNICATIONS HAND-HOLE 'HH-#1'. 4"X4"X4", REFER TO HAFB TAB K DOCUMENT SECTION 5.4.4.
- 3 EXISTING COMMUNICATIONS CONDUIT.
- 4 NEW COMMUNICATIONS CONDUIT. (2) EA 4" CONDUIT. PROVIDE (3) 1-1/4" INNERDUCT IN ONE OF THE CONDUITS. REFER TO DETAILS A3, B3 ON SHEET ES501.
- 5 NEW TRANSFORMER PROVIDED AND INSTALLED BY CITY LIGHT AND POWER.
- 6 NEW SECONDARY DUCT FROM TRANSFORMER TO 'MDP' IN ELECTRICAL ROOM. REFER TO DETAIL C5 ON SHEET ES501.
- 7 NEW PRIMARY DUCT BANK. REFER TO DETAIL C4 ON SHEET ES501.
- 8 NEW ELECTRICAL MANHOLE PROVIDED AND INSTALLED BY ELECTRICAL CONTRACTOR.
- 9 NEW 4" RISER WITH 200A CUTOFF SWITCHES PER CLP STANDARDS AT EXISTING POLE 3A57.



DATE	APPR MARK



DESIGNED BY:	PJG
CHECKED BY:	EJB
CAPITAL PROJECT NO.	1043925
OTHER PROJECT NO.	7596233
ISSUE DATE:	05/10/2022
ISSUE PROJECT MANAGER:	SCOTT ARNOLD

HAFB 309th SOFTWARE  
 ENGINEERING FACILITY  
 ELECTRICAL SITE PLAN

**ES101**  
 SHEET 102 OF 123









GENERAL SHEET NOTES




DATE	APPR MARK


SHEET KEYNOTES

1 COORDINATE FINAL LOCATION WITH MECHANICAL.

DESCRIPTION



DESIGNED BY: EJB	CAPITAL PROJECT NO. 1043925	OTHER PROJECT NO. 7596233	ISSUE DATE 05/10/2022
PROJECT NO. P/G	SITE CODE -	ISSUE DATE 05/10/2022	ISSUE DATE 05/10/2022
		DEPARTMENT OF THE AIR FORCE 75TH AIR BASE WING 75TH CIVIL ENGINEER GROUP	
SCOTT ARNOLD			



**A2 ROOF POWER PLAN**  
 EP102 SCALE: 1/8" = 1'-0"  
 NORTH

HAFB 309th SOFTWARE  
 ENGINEERING FACILITY  
 ROOF POWER PLAN

EP102  
 SHEET 105 OF 123























GENERAL SHEET NOTES


- 1 (E) DENOTES EMERGENCY FIXTURE. PROVIDE FIXTURES WITH BATTERY BACK-UP. REFER TO LIGHTING FIXTURE SCHEDULE ON EL601.




DATE	APPR MARK

SHEET KEYNOTES

- 1 COORDINATE LOCATIONS AND MOUNTING HEIGHTS OF ALL LIGHT FIXTURES IN THIS AREA WITH MECHANICAL EQUIPMENT, DUCT, PIPE, PLUMBING, ETC. PRIOR TO ROUGH-IN.
- 2 LIGHT FIXTURES WITH A SUBSCRIPT (E) ARE EGRESS FIXTURES.



DESIGNED BY:	DKM
CAPITAL PROJECT NO.:	1043925
OTHER PROJECT NO.:	7596233
ISSUE DATE:	05/10/2022
ISSUE BY:	SCOTT ARNOLD
PROJECT MANAGER:	SCOTT ARNOLD



**A2 LEVEL 1 LIGHTING PLAN**  
 EL101 SCALE: 1/8" = 1'-0"  
 NORTH

HAFB 309th SOFTWARE  
 ENGINEERING FACILITY  
 LEVEL 1 LIGHTING PLAN

EL101  
 SHEET 111 OF 123




INTERIOR LIGHTING FIXTURE SCHEDULE															GENERAL NOTES					
ABBREVIATIONS																				
<b>MOUNTING</b>			<b>LUMINAIRE OPTIONS</b>			<b>FINISH</b>			<b>DIFFUSER/LENS</b>			<b>REFLECTOR</b>			1. PROVIDE UNIT PRICES AND FIXTURE BRAND SELECTED FOR ADD/DELETE CHANGES FOR EACH FIXTURE TYPES SHOWN WITHIN 48 BUSINESS HOURS OF THE BID DATE. FAILURE TO COMPLY WITH THIS REQUIREMENT MAY DISQUALIFY THE PRODUCTS AND EMPOWER THE ENGINEER TO DETERMINE FAIR VALUE FOR FIXTURE AND INSTALLATION CHANGES, WITHOUT FURTHER INPUT FROM THE CONTRACTOR OR INSTALLER. 2. CONTRACTOR ALLOWANCE PRICES ARE ACCURATE WHEN THIS JOB WAS SPECIFIED, CONTRACTOR AND ELECTRICAL DISTRIBUTOR SHALL VERIFY THIS ALLOWANCE AND REPORT ANY PROBLEMS TO THE ENGINEER BEFORE THE BID. ALLOWANCE PRICE MAY OR MAY NOT INCLUDE LAMP(S) OR FREIGHT AS NOTED, AND DO NOT INCLUDE ANY TAXES. 3. SUBSTITUTIONS AND/OR EQUAL FIXTURES MUST RECEIVE APPROVAL PRIOR TO BIDDING, THEY MUST BE SUBMITTED TO THE ENGINEER NO LESS THAN 2 WEEKS PRIOR TO BID OPENING. 4. SAMPLES MUST BE PROVIDED FOR ANY AND ALL FIXTURES UPON A/E REQUEST PRIOR TO RELEASING FIXTURES. 5. ALL FIXTURES SHALL BE LISTED AND APPROVED FOR THEIR INTENDED USE AND LOCATION. 6. VERIFY THE PROPER MOUNTING KITS OR ACCESSORIES TO FACILITATE INSTALLATION AS SHOWN AT EACH LOCATION ON THE DRAWINGS. 7. COMPLY WITH THE "INTERIOR LIGHTING" SECTION OF THE SPECIFICATIONS. 8. REFER TO SPECIFICATIONS FOR IMPORTANT TECHNICAL REQUIREMENTS FOR LIGHTING FIXTURES, DRIVERS, AND LAMPS. 9. ALL LIGHT FIXTURES TO BE EITHER "DLC" OR "LIGHTING FACTS" LISTED OR TO BE APPROVED BY ARCHITECT/ENGINEER AND OWNER.					
B - BASE C - CEILING F - FLANGE G - GRID P - PENDANT PL - POLE R - RECESSED S - SURFACE W - WALL	ARHR - AIR RETURN AND HEAT REJECTION DL - DAMP LOCATION EQC - EARTHQUAKE CLIPS F - FUSING HLD - HINGED AND LATCHED DOOR HS - HOUSE SIDE SHIELD PS - PHOTOCCELL SWITCH QRS - QUARTZ RESTRIKE ST - STATIC WG - WIRE GUARD WL - WET LOCATION	MM - MATTE WHITE BL - BLACK SL - SILVER GL - GOLD CL - CLEAR PW - PAINTED WHITE EA - EXTRUDED ALUMINUM S - STEEL GS - GALVANIZED STEEL C - CAST CBA - COLOR BY ARCHITECT SCBA - STANDARD COLOR BY ARCHITECT CCA - CUSTOM COLOR BY ARCHITECT FS - MEETS FEDERAL STANDARD 209D TP - THERMALLY PROTECTED FL - FLUSH R - REGRESS M - MITERED	#A - ACRYLIC #THICK #OA - ACRYLIC #THICK (OPAL) GC - GLASS (CLEAR) GO - GLASS (OPAL) GF - GLASS (FROSTED) SGL - SOFT GLOW LENS HPL - HIGH PERFORMANCE LENS DO - DROP OPAL CGL - CONVEX GLASS LENS S - SATIN LENS	OP - NONE/OPEN SP - SPECULAR SS - SEMI-SPECULAR D - DIFFUSE (WHITE ENAMEL) SC - SPECULAR (COLORED) FR - PRISMATIC FDR - FULL DEPTH REFLECTOR DS - DIFFUSE (SEMI SPECULAR) SILVER LI - LOW IRIDESCENT IR - IRIDESCENT SL - SILVER GL - GOLD CA - CLEAR ALZAK																
ID	DESCRIPTION	LENGTH	DEPTH	HEIGHT	DIAMETER/APERTURE	MOUNTING	TYPE	COLOR TEMP	DRIVER CONFIGURATION	VOLTAGE	WATTS	FINISH	FIXTURE LUMENS	DIFFUSER/LENS	OPTIONS	NOTES	OPTION 1	OPTION 2	OPTION 3	OPTION 4
(DF1)	6" OPEN ROUND RECESSED DOWN LIGHT, (E) DENOTES EMERGENCY FIXTURE, PROVIDE BATTERY PACK.				6"	CR	LED	3500K	LED DRIVER	120/277	15		2400				HALO (HC615DD10 DM612835 61MDH) Q	LITHONIA LIGHTING (LDN6 35/15 L06AR LSS MVOLT GZ10) Q	LIGHTOLIER (6RN Z6RDL15835WOCZD10U)	LITON LIGHTING (CH618UE-D10/CR 6L22SW-T35)
(E1-1)	UNIVERSAL MOUNT SINGLE PHOTOLUMINESCENT EXIT SIGN	12"	8"	2"		C	LED	GREEN	LED DRIVER	120/277	3	SCBA	100				EVENLITE (LUCX-XX-XX-CBA-U-XX) Q	EMERGENSEE (SEEDLX50-P1-W-G-UB) S	MULE LIGHTING (7220-ACR-B) R	
(RL1-4)	3" WIDE EXTERIOR RECESSED LINEAR, LED, FLANGED, BLK, (E) DENOTES EMERGENCY FIXTURE, PROVIDE BATTERY PACK.	4'	2"	4"		CR	LED	4000K	LED DRIVER	120/277	20		1300	FLUSH LENS			PINNACLE (EV3-WET-840-4-FL(F)-U-OL-1) S	LUMENWERX (VIAWETR-TMG-HLO-LED-80-500-40-XFT-UNV-D1-1-TRM-BLK) R	MARK (SL2L LOP 4FT FLP FL 80CRI 35K 400LMF MIN10 277 ZT WL) J	NULITE (RXT-F-FF-03L40-1C-U-D -SCBA-4) Q
(SA1)	4" LED STRIP LIGHT, LENSED, SURFACE MOUNT OR CHAIN HUNG, (E) DENOTES EMERGENCY FIXTURE, PROVIDE BATTERY PACK.	48"					LED	4000K	LED DRIVER	120/277	30		5000				LITHONIA (ZL1D L48 3000LM FST MVOLT 40K 80CRI WH) J	ILP (VS4-25WLED-U-40-FRAL) R	METALUX (4SNLED-LD5-52SL-SLW-UNV-L840-CD1-U AYC-CHAIN/SET)	EATON (4SNLED-LD5-30-LW-UN V-L84-0-CD1) Q
(TB1)	4" LED T GRID LIGHT, INTEGRATED, NOT CLIP-ON TYPE. PROVIDE BATTERY PACK WITH EMERGENCY FIXTURES, MARKED WITH AN (E).	48"					LED	3500K	LED DRIVER	120/277	32		2300				JLC TECH (TBSL-MW-4-24-D-U-W) J	TRULY GREEN SOLUTIONS (TSPEC-4-35K-U-D) Q	SUNLITE (88792-SU / 88798-SU) R	SSCO (TLC#GL-4-20W-35 K-WH/BL-PSXXW (POWER SUPPLY))

EXTERIOR LIGHTING FIXTURE SCHEDULE															NOTES																
ABBREVIATIONS																															
<b>LUMINAIRE</b>			<b>MOUNTING</b>			<b>CONFIGURATION</b>			<b>POLE</b>			<b>BALLAST</b>			<b>FINISH</b>			<b>LENS</b>			<b>REFLECTOR AND DISTRIBUTION</b>			1. PROVIDE UNIT PRICES AND FIXTURE BRAND SELECTED FOR ADD/DELETE CHANGES FOR EACH FIXTURE TYPES SHOWN WITHIN 48 BUSINESS HOURS OF THE BID DATE. FAILURE TO COMPLY WITH THIS REQUIREMENT MAY DISQUALIFY THE PRODUCTS AND EMPOWER THE ENGINEER TO DETERMINE FAIR VALUE FOR FIXTURE AND INSTALLATION CHANGES, WITHOUT FURTHER INPUT FROM THE CONTRACTOR OR INSTALLER. 2. CONTRACTOR ALLOWANCE PRICES ARE ACCURATE WHEN THIS JOB WAS SPECIFIED, CONTRACTOR AND ELECTRICAL DISTRIBUTOR SHALL VERIFY THIS ALLOWANCE AND REPORT ANY PROBLEMS TO THE ENGINEER BEFORE THE BID. ALLOWANCE PRICE MAY OR MAY NOT INCLUDE LAMP(S) OR FREIGHT AS NOTED, AND DO NOT INCLUDE ANY TAXES.							
ARHR - AIR RETURN AND HEAT REJECTION DL - DAMP LOCATION EQC - EARTHQUAKE CLIPS F - FUSING HLD - HINGED AND LATCHED DOOR HS - HOUSE SIDE SHIELD PS - PHOTOCCELL SWITCH QRS - QUARTZ RESTRIKE ST - STATIC WG - WIRE GUARD WL - WET LOCATION	B - BASE C - CEILING F - FLANGE G - GRID P - PENDANT PL - POLE R - RECESSED S - SURFACE W - WALL	BA - BANNER ARMS BH - BULL HORN DL - 2" T SHAPE DS - 2 @ 180 PT - IN-LINE POST TOP Q - QUAD SH - SHEPHERDS HOOK SL - SINGLE T - 3" T SHAPE	RS - ROUND STRAIGHT RT - ROUND TAPERED SS - SQUARE STRAIGHT ST - SQUARE TAPERED	IS - INSTANT START RS - RAPID START PS - PROGRAM START, PARALLEL LAMP OPERATION PSMH - PULSE START METAL HALLIDE (CWA OR ELECTRONIC) PPLF - PROVIDE POWER LINE FILTER LVTM - LOW VOLTAGE TRANSFORMER (MAGNETIC) LVTE - LOW VOLTAGE TRANSFORMER (ELECTRONIC)	MM - MATTE WHITE BL - BLACK SL - SILVER GL - GOLD CL - CLEAR PW - PAINTED WHITE EA - EXTRUDED ALUMINUM S - STEEL GS - GALVANIZED STEEL C - CAST CBA - COLOR BY ARCHITECT SCBA - STANDARD COLOR BY ARCHITECT CCA - CUSTOM COLOR BY ARCHITECT FS - MEETS FEDERAL STANDARD 209D TP - THERMALLY PROTECTED FL - FLUSH R - REGRESS M - MITERED	#A - ACRYLIC #THICK #OA - ACRYLIC #THICK (OPAL) GC - GLASS (CLEAR) GO - GLASS (OPAL) GF - GLASS (FROSTED) SGL - SOFT GLOW LENS HPL - HIGH PERFORMANCE LENS DO - DROP OPAL CGL - CONVEX GLASS LENS S - SATIN LENS	I - TYPE I II - TYPE II III - TYPE III IV - TYPE IV V - TYPE V VSQ - TYPE V SQUARE SA - SPUN ALLUMINUM SR - SEGMENTED REFLECTOR BW# - NEMA BEAM WIDTH 1 THRU 7																								
1. VERIFY THE PROPER MOUNTING KITS OR ACCESSORIES TO FACILITATE INSTALLATION AS SHOWN AT EACH LOCATION ON THE DRAWINGS. 2. COMPLY WITH THE "EXTERIOR LIGHTING" SECTION OF THE SPECIFICATIONS. 3. REFER TO SPECIFICATIONS FOR IMPORTANT TECHNICAL REQUIREMENTS FOR LIGHTING FIXTURES, BALLASTS, AND LAMPS. 4. ALL FIXTURES SHALL BE APPROVED BY UL OR ANOTHER ACCEPTABLE TESTING LAB FOR THE PURPOSE INTENDED AND WITH THE LAMP AND BALLAST PROPOSED.																															
ID	TYPE	BUG RATING	UP	GLARE	LENGTH	WIDTH	DEPTH	DIAMETER/APERTURE	OPTIONS	COLOR	TYPE	INITIAL LUMENS @ 1.0BF	QUANTITY	INPUT VOLTS	ANSI WATTS	HOUSING	TRIM	TYPE	DISTRIBUTION TYPE	TYPE	CONFIGURATION	POLE BASE HEIGHT	POLE HEIGHT	WIND RATING	OPTIONS	OPTION 1	OPTION 2	OPTION 3	OPTION 4	ALLOWANCE	
(OW)	LED WALL PACK - DECORATIVE, TYPE III DISTRIBUTION, INTEGRAL PHOTO-CELL, (E) DENOTES EMERGENCY FIXTURE, PROVIDE BATTERY PACK, MOUNT AT 8'-0" AFF.									4000K	LED	2000	1	120	30												LITHONIA (WST LED P2 40K VW MVOLT)	VISIONAIRE (VSC-1-T3-16LC-3-4K-UNV -WM-CBA)	MCGRAW EDISON (IST-F01-LED-E1-BL3-CBA)	HUBBELL (TRP1-12L-20-4K7-3-U-SC BA)	

DATE	APPROVAL



DESIGNED BY: DMK	CHECKED BY: PUG	DATE: 05/10/2022
CAPITAL PROJECT NO: 1043925	SITE CODE: 1	ISSUE DATE: 05/10/2022
OTHER PROJECT NO: 7596233	PROJECT NO: KRS/MZ/00006	BASE PROJECT MANAGER: SCOTT ARNOLD



HAFB 309th SOFTWARE ENGINEERING FACILITY LIGHTING FIXTURE SCHEDULES

EL601 SHEET 112 OF 123



COMcheck Software Version 4.1.5.2  
Interior Lighting Compliance Certificate

**Project Information**  
 Energy Code: 2018 IECC  
 Project Title: HAFB New Building 309 SWEG 22-004  
 Project Type: New Construction  
 Construction Site: Owner/Agent: US AIR FORCE  
 Designer/Contractor: Doug Mabey Spectrum Engineers 324 S State St Suite 400 Salt Lake City, UT 84111 801-328-5151 dkm@spectrum-engineers.com

Credits: 1.0 Required 1.0 Proposed  
 Reduced Lighting Power, 1.0 credit

**Allowed Interior Lighting Power**

A Area Category	B Floor Area (ft <sup>2</sup> )	C Allowed Watts / ft <sup>2</sup>	D Allowed Watts (B X C)
1-Office	10157	0.71	7222
Total Allowed Watts = 7222			

**Proposed Interior Lighting Power**

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Fixture Watt. (C X D)	E (C X D)
1-Office				
LED 1: DF1: Down light: Other:	1	39	15	585
LED 2: SA1: Strip: Other:	1	10	30	300
LED 3: TB1: T-bar light: Other:	1	155	32	4960
Total Proposed Watts =				5845

Interior Lighting PASSES: Design 19% better than code

**Interior Lighting Compliance Statement**  
 Compliance Statement: The proposed interior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2018 IECC requirements in COMcheck Version 4.1.5.2 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Doug Mabey - Lighting Designer Signature Date 4/12/22

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 1 of 8

COMcheck Software Version 4.1.5.2  
Exterior Lighting Compliance Certificate

**Project Information**  
 Energy Code: 2018 IECC  
 Project Title: HAFB New Building 309 SWEG 22-004  
 Project Type: New Construction  
 Exterior Lighting Zone: 2 (Light industrial area with limited nighttime use (LZZ))  
 Construction Site: Owner/Agent: US AIR FORCE  
 Designer/Contractor: Doug Mabey Spectrum Engineers 324 S State St Suite 400 Salt Lake City, UT 84111 801-328-5151 dkm@spectrum-engineers.com

**Allowed Exterior Lighting Power**

A Area/Surface Category	B Quantity	C Allowed Watts / Unit	D Tradable Wattage	E Allowed Watts (B X C)
Main Entry (Entry canopy)	475 ft <sup>2</sup>	0.25	Yes	119
Outdoor break area (Dining area)	538 ft <sup>2</sup>	0.65	Yes	350
Pedestrian doors (Pedestrian and vehicular entrances and exits)	9 ft of door	14	Yes	126
Walkways (Walkway < 10 feet wide)	350 ft of	0.5	Yes	175
Total Tradable Watts (a) =				769
Total Allowed Supplemental Watts (b) =				400

(a) Wattage tradeoffs are only allowed between tradable areas/surfaces.  
 (b) A supplemental allowance equal to 400 watts may be applied toward compliance of both non-tradable and tradable areas/surfaces.

**Proposed Exterior Lighting Power**

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Fixture Watt.	E (C X D)
Main Entry (Entry canopy 475 ft <sup>2</sup> ): Tradable Wattage				
LED 1: RL1-4: Recessed linear: Other:	1	4	16	64
Outdoor break area (Dining area 538 ft <sup>2</sup> ): Tradable Wattage				
LED 2: SA1: Strip: Other:	1	2	30	60
Pedestrian doors (Pedestrian and vehicular entrances and exits 9 ft of door width): Tradable Wattage				
LED 3: OW: Wall Pack: Other:	1	3	25	75
Walkways (Walkway < 10 feet wide 350 ft of walkway length): Tradable Wattage				
LED 4: OW: Wall Pack: Other:	1	5	25	125
Total Tradable Proposed Watts =				324

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 2 of 8

Exterior Lighting PASSES: Design 72% better than code  
**Exterior Lighting Compliance Statement**  
 Compliance Statement: The proposed exterior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed exterior lighting systems have been designed to meet the 2018 IECC requirements in COMcheck Version 4.1.5.2 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.  
 Doug Mabey - Lighting Designer Signature Date 4/12/22

COMcheck Software Version 4.1.5.2  
Inspection Checklist

Energy Code: 2018 IECC  
 Requirements: 0.0% were addressed directly in the COMcheck software  
 Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
C103.2 [PR4]	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the interior lighting and electrical systems and equipment and document where exceptions to the standard are claimed. Information provided should include interior lighting power calculations, wattage of bulbs and ballasts, transformers and control devices.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C103.2 [PR6]	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the exterior lighting and electrical systems and equipment and document where exceptions to the standard are claimed. Information provided should include exterior lighting power calculations, wattage of bulbs and ballasts, transformers and control devices.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

**Additional Comments/Assumptions:**

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 4 of 8

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
C405.2.2 [EL22] <sup>2</sup>	Spaces required to have light-reduction controls have a manual control that allows the occupant to reduce the connected lighting load in a reasonably uniform illumination pattern >= 50 percent.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.1 [EL18] <sup>1</sup>	Occupancy sensors installed in classrooms/lecture/training rooms, conference/meeting/multipurpose rooms, copy/print rooms, lounges/breakrooms, enclosed offices, open plan office areas, restrooms, storage rooms, locker rooms, warehouse storage areas, and other spaces <= 300 sq ft that are enclosed by floor-to-ceiling height partitions. Reference section language C405.2.1.2 for control function in warehouses and section C405.2.1.3 for open plan office spaces.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.1 [EL19] <sup>2</sup>	Occupancy sensors control function in warehouses. In warehouses, the lighting in aiseways and open areas is controlled with occupant sensors that automatically reduce lighting power by 50% or more when the areas are unoccupied. The occupant sensors control lighting in each aisleway independently and do not control lighting beyond the aisleway being controlled by the sensor.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.1 [EL20] <sup>3</sup>	Occupant sensor control function in open plan office areas: Occupant sensor controls in open office spaces >= 300 sq ft. have controls 1) configured so that general lighting can be controlled separately in control zones with floor areas <= 600 sq ft. within the space, 2) automatically turn off general lighting in all control zones within 20 minutes after all occupants have left the space, 3) are configured so that general lighting power in each control zone is reduced by >= 80% of the full zone general lighting power within 20 minutes of all occupants leaving that control zone, and 4) are configured such that any daylight responsive control will activate space general lighting or control zone general lighting only when occupancy for the same area is detected.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.2 [EL21] <sup>2</sup>	Each area not served by occupancy sensors (per C405.2.1) have time-switch controls and functions detailed in sections C405.2.2.1 and C405.2.2.2	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 5 of 8

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
C405.2.3 [EL23] <sup>2</sup>	Daylight zones provided with individual controls that control the lights independent of general area lighting. See code section C405.2.3 Daylight-responsive controls for applicable spaces, C405.2.3.1 Daylight-responsive control function and section C405.2.3.2 Sidelit zone.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.4 [EL26] <sup>1</sup>	Separate lighting control devices for specific uses installed per approved lighting plans.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.4 [EL27] <sup>1</sup>	Additional interior lighting power allowed for special functions per the approved lighting plans and is automatically controlled and separated from general lighting.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.2.5 [EL28] <sup>1</sup>	Automatic lighting controls for exterior lighting installed. Controls will be daylight controlled, set based on business operation time-of-day, or reduce connected lighting >= 30%.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.3 [EL6] <sup>3</sup>	Exit signs do not exceed 5 watts per face.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

**Additional Comments/Assumptions:**

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 6 of 8

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C403.3 [F117] <sup>2</sup>	Furnished O&M instructions for systems and equipment to the building owner or designated representative.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C405.4.1 [F118] <sup>1</sup>	Interior installed lamp and fixture lighting power is consistent with what is shown on the approved lighting plans, demonstrating proposed watts are less than or equal to allowed.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Interior Lighting fixture schedule for values.
C405.5.1 [F119] <sup>1</sup>	Exterior lighting power is consistent with what is shown on the approved lighting plans, demonstrating proposed watts are less than or equal to allowed watts.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Exterior Lighting fixture schedule for values.
C408.2.5 [F116] <sup>1</sup>	Furnished as-built drawings for electric power systems within 90 days of system acceptance.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C408.3 [F133] <sup>1</sup>	Lighting systems have been tested to ensure proper calibration, adjustment, programming, and operation.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

**Additional Comments/Assumptions:**


1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 7 of 8

Project Title: HAFB New Building 309 SWEG 22-004 Report date: 04/12/22  
 Data filename: P:\2022\220057\2Design\4COMcheck\HAFB SWEG.cck Page 8 of 8



DATE	APPROVAL MARK



DESIGNED BY: DKM	CAPITAL PROJECT NO: 1043925	OTHER PROJECT NO: 7596233	ISSUE DATE: 05/10/2022
PAG: 1	SITE CODE: 1	BASE PROJECT NUMBER: KRS/MZ/00006	ISSUE PROJECT NUMBER: 5263908-2202
SCOTT ARNOLD	DEPARTMENT OF THE AIR FORCE 75TH AIR BASE WING 75TH CIVIL ENGINEER GROUP		

HAFB 309th SOFTWARE ENGINEERING FACILITY LIGHTING COMCHECK

EL602 SHEET 113 OF 123




LIGHTING/SPACE CONTROL TYPE SCHEDULE

WIRING LEGEND		APPROVED MANUFACTURERS	LIGHTING CONTROL ID	GENERAL NOTES										GENERAL NOTES									
_____ LINE VOLTAGE WIRING - - - - - 0-10V WIRING - - - - - CAT5E CABLING _____ WIRING BY OTHERS ○-○ TWP SEGMENT NETWORK CABLING		1. WATTSTOPPER (BASIS OF DESIGN) 2. NLIGHT 3. HUBBELL BUILDING AUTOMATION 4. GREENGATE	1. # = NUMBER OF ZONES 2. D = DIMMING, S = SWITCHING 3. P = DAYLIGHT PHOTOCELL 4. L = PLUG LOAD CONTROLLER 5. # = INSTANCE	1. COORDINATE INITIAL PROGRAMMING WITH OWNER AND MODIFY CONTROL TIMES AND OPERATION AS REQUESTED BY OWNER. 2. PROVIDE FINE TUNING PROGRAMMING AND ADJUSTMENTS UPON REQUEST BY OWNER WITHIN FIRST 6 MONTHS AFTER SUBSTANTIAL COMPLETION. 3. PROVIDE CUSTOMIZED ENGRAVED PERMANENT BUTTON LABELS ON EACH SWITCH, LABEL TO MATCH BUTTON LABEL ID OR AS DIRECTED BY OWNER. 4. PART NUMBERS SHOWN ARE BASED ON WATTSTOPPER AS THE BASIS OF DESIGN. ALL APPROVED MANUFACTURERS ARE SUBJECT TO MEETING ALL FUNCTIONS AND CAPABILITIES OF THE BASIS OF DESIGN SYSTEM AND PRODUCTS. FAILURE TO MEET THESE SHALL REQUIRE THE CONTRACTOR TO PROVIDE A SYSTEM THAT DOES AT NOT ADDITIONAL COST.										5. REFER TO PLANS FOR LOCATIONS AND QUANTITIES OF DEVICES. 6. INSTALL ONE OF EACH CONTROL TYPE WITH PROGRAMMING, ADJUST, AND OBTAIN OWNERS APPROVAL PRIOR TO PROGRAMMING THE REMAINING CONTROLS. 7. WIRING MAY VARY BETWEEN MANUFACTURERS. CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE REQUIRED WIRING THAT WILL BOTH MEET THE MANUFACTURERS REQUIREMENTS AND MATCH WITH THE SHOWN SYSTEM. 8. PROVIDE COMPLETE SHOP DRAWING SUBMITTALS INCLUDING OCCUPANCY SENSOR LAYOUT AND COVERAGE PATTERNS. PROVIDE ADDITIONAL SENSORS AS REQUIRED FOR 100% COVERAGE OF SPACES WITH OCCUPANCY SENSOR CONTROL.									
ID	DETAIL	LIGHTS ON CONTROL	LIGHTS OFF CONTROL	LIGHTING CONTROL TYPE	DAYLIGHT SENSOR SETTING (FC)	TIME DELAY TO OFF (MIN.)	BAS AUX RELAY SIGNAL	PLUG LOAD CONTROLLER	NETWORKED CONTROLS	BUTTON_1	BUTTON_2	BUTTON_3	BUTTON_4	BUTTON_5	BUTTON_6	BUTTON_7	BUTTON_8	BUTTON_9	NOTES				
1D1		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	DIMMING 0-10V	-	15	RELAY CLOSED ON OCCUPANCY	-	-	FUNCTION: PRESS TOP-ON, HOLD TOP-RAISE LABEL ID: TOP. "ON/RAISE" BOTTOM-"OFF/LOWER"													
1S1		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	ON/OFF	-	15	RELAY CLOSED ON OCCUPANCY	-	-	FUNCTION: PRESS-ON PRESS-OFF LABEL ID: "ON/OFF"													
2D1		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	DIMMING 0-10V	-	15	RELAY CLOSED ON OCCUPANCY	-	-	TOGGLE PRESS TOP-ON, PRESS BOTTOM-OFF, HOLD TOP-RAISE, HOLD BOTTOM-"OFF/LOWER"	FUNCTION: PRESET SCENE #01 ZONE "a" 75% DIMMING LABEL ID: "PRE #1"	FUNCTION: PRESET SCENE #02 ZONE "a" 0% DIMMING LABEL ID: "PRE #2"	FUNCTION: PRESS-SELECT ZONE "a" FOR DIMMING LABEL ID: "ZONE a"	FUNCTION: PRESS-SELECT ZONE "b" FOR DIMMING LABEL ID: "ZONE b"	-	-	-	-	-				



DATE	APPR MARK



DESIGNED BY: DKM	PROJECT NO: 1043925	ISSUE DATE: 05/10/2022
CHECKED BY: PUG	ISSUE NO: 1	ISSUE DATE: 05/10/2022
CAPITAL PROJECT NO: 1043925	OTHER PROJECT NO: 7596233	ISSUE PROJECT MANAGER: SCOTT ARNOLD
DEPARTMENT OF THE AIR FORCE 75TH AIR BASE WING 75TH CIVIL ENGINEER GROUP		

HAFB 309th SOFTWARE ENGINEERING FACILITY  
 LIGHTING CONTROL SCHEDULES

EL603  
 SHEET 114 OF 123



LIGHTING/SPACE CONTROL TYPE SCHEDULE

WIRING LEGEND		APPROVED MANUFACTURERS	LIGHTING CONTROL ID	GENERAL NOTES										GENERAL NOTES									
_____ LINE VOLTAGE WIRING - - - - - 0-10V WIRING - - - - - CAT5E CABLING _____ WIRING BY OTHERS ○-○ TWP SEGMENT NETWORK CABLING		1. WATTSTOPPER (BASIS OF DESIGN) 2. NLIGHT 3. HUBBELL BUILDING AUTOMATION 4. GREENGATE	1. # = NUMBER OF ZONES 2. D = DIMMING, S = SWITCHING 3. P = DAYLIGHT PHOTOCELL 4. L = PLUG LOAD CONTROLLER 5. # = INSTANCE	1. COORDINATE INITIAL PROGRAMMING WITH OWNER AND MODIFY CONTROL TIMES AND OPERATION AS REQUESTED BY OWNER. 2. PROVIDE FINE TUNING PROGRAMMING AND ADJUSTMENTS UPON REQUEST BY OWNER WITHIN FIRST 6 MONTHS AFTER SUBSTANTIAL COMPLETION. 3. PROVIDE CUSTOMIZED ENGRAVED PERMANENT BUTTON LABELS ON EACH SWITCH, LABEL TO MATCH BUTTON LABEL ID OR AS DIRECTED BY OWNER. 4. PART NUMBERS SHOWN ARE BASED ON WATTSTOPPER AS THE BASIS OF DESIGN. ALL APPROVED MANUFACTURERS ARE SUBJECT TO MEETING ALL FUNCTIONS AND CAPABILITIES OF THE BASIS OF DESIGN SYSTEM AND PRODUCTS. FAILURE TO MEET THESE SHALL REQUIRE THE CONTRACTOR TO PROVIDE A SYSTEM THAT DOES AT NOT ADDITIONAL COST.										5. REFER TO PLANS FOR LOCATIONS AND QUANTITIES OF DEVICES. 6. INSTALL ONE OF EACH CONTROL TYPE WITH PROGRAMMING, ADJUST, AND OBTAIN OWNERS APPROVAL PRIOR TO PROGRAMMING THE REMAINING CONTROLS. 7. WIRING MAY VARY BETWEEN MANUFACTURERS. CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE REQUIRED WIRING THAT WILL BOTH MEET THE MANUFACTURERS REQUIREMENTS AND MATCH WITH THE SHOWN SYSTEM. 8. PROVIDE COMPLETE SHOP DRAWING SUBMITTALS INCLUDING OCCUPANCY SENSOR LAYOUT AND COVERAGE PATTERNS. PROVIDE ADDITIONAL SENSORS AS REQUIRED FOR 100% COVERAGE OF SPACES WITH OCCUPANCY SENSOR CONTROL.									
ID	DETAIL	LIGHTS ON CONTROL	LIGHTS OFF CONTROL	LIGHTING CONTROL TYPE	DAYLIGHT SENSOR SETTING (FC)	TIME DELAY TO OFF (MIN.)	BAS AUX RELAY SIGNAL	PLUG LOAD CONTROLLER	NETWORKED CONTROLS	BUTTON_1	BUTTON_2	BUTTON_3	BUTTON_4	BUTTON_5	BUTTON_6	BUTTON_7	BUTTON_8	BUTTON_9	NOTES				
3DP1		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	DIMMING 0-10V	30	15	RELAY CLOSED ON OCCUPANCY	-	-	TOGGLE PRESS TOP-ON, PRESS BOTTOM-OFF, HOLD TOP-RAISE, HOLD BOTTOM-LOW ER	PRESET SCENE #01 - ZONE "a" 0%, ZONE "b" 50%, ZONE "c" 100%	SELECT ZONE "a"	SELECT ZONE "b"	SELECT ZONE "c"	-	-	-	-	-	-			
4DP1		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	DIMMING 0-10V	30	15	RELAY CLOSED ON OCCUPANCY	-	-	FUNCTION: PRESS TOP-ON, HOLD TOP-RAISE PRESS BOTTOM-OFF, HOLD BOTTOM-LOW ER LABEL ID: TOP- "ON/RAISE" BOTTOM-"OFF/ LOWER"	FUNCTION: PRESS-SELEC T ZONE "a" FOR DIMMING LABEL ID: "ZONE a"	FUNCTION: PRESS-SELEC T ZONE "b" FOR DIMMING LABEL ID: "ZONE b"	FUNCTION: PRESS-SELEC T ZONE "c" FOR DIMMING LABEL ID: "ZONE c"	FUNCTION: PRESS-SELEC T ZONE "d" FOR DIMMING LABEL ID: "ZONE d"	FUNCTION: PRESS-PRES T SCENE #01 ZONE "a" 75% ZONE "b" 75% ZONE "c" 75% ZONE "d" 75% LABEL ID: "PRE #1"	FUNCTION: PRESS-PRES T SCENE #02 ZONE "a" 50% ZONE "b" 50% ZONE "c" 50% ZONE "d" 50% LABEL ID: "PRE #2"	FUNCTION: PRESS-PRES T SCENE #03 ZONE "a" 0% ZONE "b" 100% ZONE "c" 100% ZONE "d" 0% LABEL ID: "PRE #3"	FUNCTION: PRESS-PRES T SCENE #04 ZONE "a" 0% ZONE "b" 50% ZONE "c" 50% ZONE "d" 100% LABEL ID: "PRE #4"	MODE 1-ROOM OPERATE INDIVIDUALLY MODE 2-ROOMS OPERATE COMBINED, AV INTEGRATION REQUIRED, PARTITION SENSING REQUIRED				



DATE	APPR	MARK



DESIGNED BY:	DKM
CHECKED BY:	SCOTT ARNOLD
PROJECT NO.:	1043925
ISSUE DATE:	05/10/2022
ISSUE NO.:	1
ISSUE BY:	SCOTT ARNOLD

DEPARTMENT OF THE AIR FORCE  
 75TH AIR BASE WING  
 75TH CIVIL ENGINEER GROUP

HAFB 309th SOFTWARE  
 ENGINEERING FACILITY  
 LIGHTING CONTROL SCHEDULES

EL604  
 SHEET 115 OF 123